12Vdc 5A Model

PART No:

TPS12-5DC



Security Power Supplies

© 2024 The contents of this manual are copyright and may not be reproduced without the written permission of Tactical Power Products Pty Ltd.



TPS12-5DC, Small Kit and PDM5 Shown









12Vdc5A Series



Specifications:

(In the interests of product improvement, Tactical reserves the right to change specifications without notice)

Eco Range®	5DC	5DC + Small Kit	5DC+ Small Kit + PDM5-500	5DC+ Medium Kit	5DC + Medium Kit + PDM5-500
Output Voltage	12 Vdc				
Output Current	5A Continuous				
Output Channels	1	1	10	1	10
Output per Channel	5A	5A	500mA	5A	500mA
Input Voltage	240 V ac(+6% / -10%)50Hz				
Input Current	0.8A @ full load				
Input In-Rush Current	<20A (25° C cold start up)				
Battery Charger	13.8Vdc / 1.4A (Max)				
Low Battery Indicator	1 x SPDT relay & Red LED				
AC Input Indicator	1 x SPDT Relay & Green LED				
Weight (Approx)	1.2Kg	4Kg		6Kg	
Dimensions (mm)	226L x 123W x 60H	250W x 310H x 100D		340W x 436H x 145D	
Overload Protection	Hysteretic thermal shutdown with automatic fault recovery				
Load Regulation	< 1% from open to full load				
Line Regulation	< 0.2%				
Output Ripple	25mV p-p @ full load (Typical)				
Working Temperature	0 - 50° C WITHOUT DERATING				
Revision	E.				
Safety Standards	Safety Standard AS NZS 62368:1:2022 Certificate of Approval EESS-240725-0				
EMC Standards	AS/NZS CISPR 11:2004(Class B Conducted and Radiated)				



www.tacpower.com.au

Securing Your Power Needs ® Now and into the Future...



Tel: 1300-822-769 | U23/9-12 Lambridge Pl. Penrith 2750 | <u>sales@tacpower.com.au</u>